

2022 - 602 CRATE MODIFIED RULES

To be eligible for competition, all cars must meet requirements set forth in either the current NASCAR rulebook or R.O.C. rulebook as far as body, chassis, and drive train is concerned. The only exceptions will be that the engine, clutch, ignition, weight, wheel, and tire specifications will be replaced with the following:

WHEELS AND TIRES

NOTE: Hoosier F45 are available at the track.

1. Only 15" diameter by 10" width five lug reinforced magnetic steel racing wheels permitted.
2. Any offset permitted.
3. Only solid one piece, heavy duty 5/8" magnetic steel lug bolts and standard one inch hex, fully threaded and solid magnetic steel lug nuts will be permitted.
4. No bead lock wheels permitted.
5. 84" tread width at bead, at Spindle height, at front and rear. Minimum wheelbase of 107"

WEIGHT

GM Sealed crate motors must way a minimum of 2550lbs after race with driver and 58% left side.

Wall Speedway, Stafford Speedway(SK Lights) Sealed crate motors minimum of 2650lbs after race with driver and 56% left side.

No unsealed motors. Must provide track rulebook for home track seal.

Any bolted on weight must be painted white and have car number on it.

ENGINE - Crate Engine 350/350 88958602. Compression based on home track rule. Valve springs 80lb @1.700

CARBURETORS – 650 H.P. Carb only – Part #80541-1, must remain stock. 1" spacer maximum

DISTRIBUTOR – Stock type HEI Distributor. No MSD box. Vacuum advance may be removed. Rev limiter allowed.

TRANSMISSION - Only standard production OEM type Muncie or T-10 manual for speed transmissions will be permitted. No Jericho Transmissions permitted. Only a one piece magnetic steel drive shaft, painted white, will be permitted.

CLUTCH – 10" diameter. No carbon fiber clutch parts.

7.25" clutch may be used, must add 100 lbs

-5.5" clutch may not be used

Bell housing must have opening for visual inspection

Bell housing must be magnetic steel only

Bell housing must be magnetic steel only

REAR AXLE –NO TITANIUM AXLES ALLOWED IN ANY CAR. No Lockers, Locked Spool only
5.60 max gear ratio

MUFFLERS/HEADERS - Mufflers are MANDATORY on ALL cars. No Tri Y or Stainless Headers

SHOCKS – No adjustable shocks, no external shruader valves, no nitrogen filled shocks, no external reservoirs permitted. Maximum net per shock \$225

DRIVE SHAFTS – The drive shaft, universal joints, and yokes must be magnetic steel and be similar in

design to the standard production type. Only a one piece magnetic steel drive shaft, painted white, will be permitted

SPOILERS - For all cars, spoiler must be a maximum of 8 inches high by a maximum of 48 inches wide. The rear spoiler may not extend past the rear edge of the rear bumper at any time. A maximum of 35 ½ inches, measured from the ground to the spoiler mounting point-will be permitted. Rear spoiler must be solid clear polycarbonate (minimum ¼ inch thick). No lettering is allowed on spoiler.

FUEL CELLS - Maximum capacity is 22 gallons

SCANNERS/RADIOS/MIRRORS- Driver must have scanner and monitor race director and tower at all times. Scanner must be onboard racecar and operational at all times. Two way radios and mirrors re allowed.

Must be 12 years of age or older to compete in this class. Drivers under 14 must be approved by the track.

OVERLY COMPETITIVE CARS ARE SUBJECT TO INSPECTION AT ANY TIME

NOTE: Enforcement and interpretation of all rules is subject to the discretion of Evergreen Raceway officials. All Evergreen Raceway gauges, scales, and measuring equipment will be the absolute last word in any and all disputes.